

# HT250U 15" RIDE HEIGHT UNDERSLUNG SUSPENSION PSI / LOAD SCALE

<b>Req'd psi</b>	<b>Load per axle (lbs)</b>	<b>Load per axle (kg)</b>
<b>90</b>	<b>25,000</b>	<b>11,340</b>
<b>83</b>	<b>23,000</b>	<b>10,433</b>
<b>75</b>	<b>21,000</b>	<b>9,525</b>
<b>68</b>	<b>19,000</b>	<b>8,618</b>
<b>61</b>	<b>17,000</b>	<b>7,711</b>
<b>54</b>	<b>15,000</b>	<b>6,804</b>
<b>47</b>	<b>13,000</b>	<b>5,897</b>
<b>39</b>	<b>11,000</b>	<b>4,990</b>
<b>32</b>	<b>9,000</b>	<b>4,082</b>
<b>25</b>	<b>7,000</b>	<b>3,175</b>
<b>18</b>	<b>5,000</b>	<b>2,268</b>

For Air Spring Part Number C-13122

Trailer Suspension Systems  
2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
800.RIDEAIR (743.3247)  
330.489.0045  
Fax 800.696.4416



Trailer Suspension Systems  
250 Chrysler Drive, Unit #3  
Brampton, ON L6S 6B6 Canada  
905.789.1030  
Fax 905.789.1033

[www.hendrickson-intl.com](http://www.hendrickson-intl.com)