HENDRICKSON USE ONLY

ORDERING GUIDE

HT™ SERIES 25K/30K UNDERSLUNG and Y-BEAM SUSPENSIONS

LIT NO: L555
DATE: December 2015 **REVISION:** H

FORM INSTRUCTIONS

For complete price and model number information on an HT250US, HT300US or HT300YB suspension, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		**FROM:**		**COMPANY NAME:**	
DATE		**PHONE:**		**FAX:**	
EMAIL:					
SAME AS:		**EXCEPT:**			

SUSPENSION

SUSPENSION MODEL (capacity):	☐ HT250US (25K)	☐ HT300US (30K)				
AXLE CONNECTION:	None					
RIDE HEIGHT: (inches)	☐ 3.5" (25K only)	☐ 4" (25K only)	☐ 5.5"	☐ 6.5"	☐ 7.5"	☐ 9"
	☐ 12"	☐ 14"	☐ 17" (30K only)			
TRAVEL:	☐ Standard	☐ Limited Jounce	☐ Extended Rebound			
FRAME BRACKET:	☐ Weld-On	☐ Bolt-On	☐ Other			
	MOUNTING BOLT SIZE:	☐ 0.500"	☐ 0.625"[1]			
AIR SPRING PSI RANGE:	☐ Standard	☐ High Pressure (25K only)				
AIR SPRING MOUNTING PLATE:	☐ Standard	☐ Rotated (25K only)	☐ None			
SHOCK ABSORBER:	☐ Standard	☐ Extended Service / High Damping[1]				
SHOCK MOUNT:	☐ Standard Mount	☐ Remote Mount				
SHOCK STRAPS:	☐ Yes	☐ No				
FRAME BRACKET TO BEAM:	☐ Assembled	☐ Non-Assembled				
TIRE SIZE (inches): (To determine U-bolt)	☐ 17.5" (25K only)	☐ 19.5" or larger				
C-CHANNEL:	☐ Standard Weld-on	☐ Customer Supplied				
HIGH CONTROL SUSPENSION[2]:	☐ Yes	☐ No				
AXLE STYLE:	☐ Standard	☐ Steerable (25K only)				
BRAKE TYPE:	Drum Only (Air disc brakes not available)					
SUSPENSION COATING:	☐ Standard Black Primer	☐ None				
FRAME BRACKET COATING:	☐ Standard Black Primer	☐ None / Do not paint frame brackets				

STOP **Are you ordering a Y-Beam suspension?** ☐ **No** ☐ **Yes (continue to page 2)**

1. Required for HT300US suspension.
2. High control suspensions are recommended for single-axle trailers in multi-trailer combinations, all dollies and full trailers with two single axles. Not for use on multiple-axle trailers.

NOTE: Some combinations may not be compatible or available.

HENDRICKSON

SUSPENSION

SUSPENSION MODEL (capacity):	☐ HT300YB[3] (30K Y-Beam)
AXLE CONNECTION:	None
RIDE HEIGHT (inches):	☐ 6.5" ☐ 7.5" ☐ 9"
TRAVEL:	Standard
FRAME BRACKET:	Y-Beam
AIR SPRING PSI RANGE:	Standard
AIR SPRING MOUNTING PLATE:	☐ Standard ☐ None
SHOCK ABSORBER:	Standard
SHOCK MOUNT:	Standard
SHOCK STRAPS:	☐ Yes ☐ No
FRAME BRACKET TO BEAM:	Non-Assembled
TIRE SIZE (inches):	19.5" or larger
C-CHANNEL:	None (Y-Beam)
HIGH CONTROL SUSPENSION:	No
AXLE STYLE:	Standard
BRAKE TYPE:	Drum Only (Air disc brakes are not available)
SUSPENSION COATING:	☐ Standard Black Primer ☐ None
FRAME BRACKET COATING:	None

3. For use in conjunction with HT300US suspensions.

E-mail This Form Print Form

*Call your trailer dealer or Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.*

HENDRICKSON

www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS
2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada
250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana
Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601

L555 Rev H 12-15

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected. © 2015 Hendrickson USA, L.L.C. All Rights Reserved

Printed in United States of America