

# HT300US/HT300YB UNDERSLUNG SUSPENSION PSI / LOAD SCALE

| Req'd psi | Load per axle<br>(lbs) | Load per axle<br>(kg) |
|-----------|------------------------|-----------------------|
| 79        | 30,000                 | 13,608                |
| 73        | 28,000                 | 12,701                |
| 68        | 26,000                 | 11,793                |
| 62        | 24,000                 | 10,886                |
| 57        | 22,000                 | 9,979                 |
| 51        | 20,000                 | 9,072                 |
| 46        | 18,000                 | 8,165                 |
| 40        | 16,000                 | 7,257                 |
| 35        | 14,000                 | 6,350                 |
| 29        | 12,000                 | 5,443                 |
| 24        | 10,000                 | 4,536                 |
| 18        | 8,000                  | 3,629                 |
| 13        | 6,000                  | 2,722                 |
| 7         | 4,000                  | 1,814                 |

For Air Spring Part Number: C-25319

**Trailer Commercial  
Vehicle Systems**

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.(RIDEAIR) 743.3247  
330.489.0045  
Fax 800.696.4416



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**Hendrickson Canada**

250 Chrysler Drive, Unit #3  
Brampton, ON L6S 6B6 Canada  
800.668.5360  
905.789.1030  
Fax 905.789.1033