

HENDRICKSON USE ONLY

Kit Part No.:

Kit Price:

H ORDERING GUIDE
TIREMAAX® TIRE INFLATION SYSTEM

LIT NO: L868

DATE: March 2017

REVISION: 0

FORM INSTRUCTIONS

For complete price and model number information for a TIREMAAX® system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		FROM:		COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:		

SAME AS:	EXCEPT:
-----------------	----------------

TIREMAAX®¹ (Continued on page 2)

CONTROLLER TYPE:	<input type="checkbox"/> CP	<input type="checkbox"/> PRO
ELECTRICAL CONNECTION:	<input type="checkbox"/> Delphi Weather Pack (Standard)	<input type="checkbox"/> Blade Terminals ² (Hendrickson Controls approval required)
KIT STYLE:	<input type="checkbox"/> For OEM Installation	<input type="checkbox"/> For Aftermarket / Retrofit Installation
AXLE STYLE:	<input type="checkbox"/> Integrated (INTRAAX®, VANTRAAX®, etc.)	
	<input type="checkbox"/> Standard (Hendrickson TRLAXLE®)	Standard Axle Track: <input type="checkbox"/> 71.5" to 83" <input type="checkbox"/> 83.5" to 92"
AXLE PREPARATION:	<input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Hendrickson (Kit includes controller and tire hoses only.)	
	<input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Trailer OEM (Kit includes controller, hubcap assemblies and tire hoses.)	
	<input type="checkbox"/> Not Prepped for TIREMAAX (Select for Aftermarket / Retrofit applications; Kit includes controller, hubcap assemblies, tire hoses and axle kit.)	
NUMBER OF AXLES:	<input type="checkbox"/> 1	<input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> Other:
SPINDLE STYLE:	<input type="checkbox"/> HN	<input type="checkbox"/> HP
HUBCAP TYPE:	<input type="checkbox"/> Hendrickson Bolt-On	<input type="checkbox"/> Hendrickson Extended Bolt-On ³
LUBE TYPE:	<input type="checkbox"/> Semi-Fluid Grease	<input type="checkbox"/> Oil
WHEEL STYLE / MATERIAL	<input type="checkbox"/> Dual / Aluminum	<input type="checkbox"/> Dual / Steel or Combo
	<input type="checkbox"/> Super Single / Steel (outboard valve stem; 180-degree hose)	<input type="checkbox"/> Super Single / Aluminum (straight hose)
	<input type="checkbox"/> Super Single / Steel (inboard valve stem; straight hose)	
TIRE SIZE:	<input type="checkbox"/> 17.5"	<input type="checkbox"/> 19.5" <input type="checkbox"/> 22.5" <input type="checkbox"/> 24.5"
COLD TIRE PRESSURE SETTING (psi)⁴:	<input type="checkbox"/> 70 <input type="checkbox"/> 75 <input type="checkbox"/> 80 <input type="checkbox"/> 85 <input type="checkbox"/> 90 <input type="checkbox"/> 95 <input type="checkbox"/> 100 <input type="checkbox"/> 105 <input type="checkbox"/> 110 <input type="checkbox"/> 115 <input type="checkbox"/> 120	

- Hendrickson does not provide warranty coverage for the installation, performance or components of a competitor brand tire inflation system installed on a Hendrickson suspension or trailer axle. Any consequential damages to the Hendrickson suspension or trailer axle resulting from a failure to the competitor brand tire inflation system or components, whether installed by the OEM, repair facility or end-user customer, should be directed to the respective tire inflation system manufacturer for warranty coverage.
- Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".
- Required for axles with TIREMAAX PRO equipped with cross-drilled spindles and using the castellated spindle nut. Please verify spindle nut requirements.
- Refer to tire manufacturer's recommended tire pressure. TIREMAAX PRO is restricted to cold tire pressure setting of 85-120 psi.



TIREMAAX®*(Continued from page 1)*

TRAILER-MOUNTED INDICATOR LIGHT KIT:	<input type="checkbox"/> LED – 12V with 65-foot Cable (Standard) <input type="checkbox"/> Incandescent – 12V	<input type="checkbox"/> LED – 12V with 35-foot Cable <input type="checkbox"/> No ²	<input type="checkbox"/> LED – 24V (Export ⁵)
WIRING HARNESS:	<input type="checkbox"/> Premium, 15-Foot, ABS-ready <input type="checkbox"/> Standard, 18-inch, Wiring Adapter Plug	<input type="checkbox"/> Premium, 3-Foot, ABS-ready <input type="checkbox"/> No ² (Hendrickson Controls approval required)	
AIR PLUMBING KIT:	<input type="checkbox"/> Manifold ⁶	<input type="checkbox"/> No	
CONTROLLER TANK VALVE⁷: (Pressure Check)	<input type="checkbox"/> Yes (CP Models Only)	<input type="checkbox"/> No	

5. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

6. Not available for single-axle systems.

7. Not available with TIREMAAX PRO.

Call your trailer dealer or Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
800.668.5360
905.789.1030 • Fax 905.789.1033

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601