

# **HHT™ SERIES**

## **HT300US SPECIFICATIONS**

LIT NO: L1229

DATE: March 2015

REVISION: A

---





APPLICATIONS													
<b>*CAPACITY</b>	30,000 lbs. (13 600 kg)												
<b>TRAILER TYPES</b>	<table border="0"> <tr> <td>Chip Van</td> <td>Platform</td> </tr> <tr> <td>Flat</td> <td>Auto Hauler</td> </tr> <tr> <td>Lowboy/Drop Deck</td> <td>Container Chassis</td> </tr> <tr> <td>Dump</td> <td>Logging</td> </tr> <tr> <td>Tanker</td> <td>Livestock</td> </tr> <tr> <td>Grain</td> <td></td> </tr> </table> <p><i>Refer to "L707 Application Guide" for Recommended Applications</i></p>	Chip Van	Platform	Flat	Auto Hauler	Lowboy/Drop Deck	Container Chassis	Dump	Logging	Tanker	Livestock	Grain	
Chip Van	Platform												
Flat	Auto Hauler												
Lowboy/Drop Deck	Container Chassis												
Dump	Logging												
Tanker	Livestock												
Grain													
<b>AXLE DATA</b>	5-inch diameter round, 3/4-inch wall, 15-inch and 16.5-inch brakes												
<b>AXLE ARRANGEMENT</b>	Single, tandem: 122-inch maximum axle spacing Tri or quad: 144-inch maximum total spacing												
<b>FRAME TYPES</b>	Steel only; 96-inch or 102-inch wide trailers												
<b>BASE MODEL DESCRIPTION:</b>	HT™ Series underslung standard travel suspension, 6.5-inch ride height, weld-on, wingless frame brackets with QUIK-ALIGN® and forward mounted shocks standard with shock straps.												
<b>**BASE MODEL WEIGHT:</b>	375 lbs.												
<b>OTHER OPTIONS:</b>	Additional options include bolt-on frame brackets, remote mount shock absorbers and limited jounce travel. Contact your Hendrickson representative to discuss these and other product options such as pre-torqued pivot bolts.												

\* Capacity refers to suspension ratings, except where noted. Ratings for brakes and wheel-end components differ depending upon options chosen.

\*\* Weight shown does not include the axle or the frame bracket crossmember.

## SPECIFICATIONS

SUSPENSION — HT300US		
RIDE HEIGHT (inches)	JOUNCE <sup>1,2</sup> (inches)	REBOUND <sup>1,2</sup> (inches)
5.5	2.0	4.7
6.5	3.0	3.7
7.5	3.1	6.0
9.0	4.6	4.5
12.0	4.9	4.0
14.0	5.0	4.0
17.0	5.5	3.5

<sup>1</sup> Jounce, rebound and weight figures shown are for models with standard weld-on hangers and standard shock absorbers. These values differ slightly for other models and options. Contact Hendrickson for more information.

<sup>2</sup> Limited axle travel configurations and extended rebound 6.5-inch ride height models are also available.

Call your trailer dealer or Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

### TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

### Hendrickson Canada

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

### Hendrickson Mexicana

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601