




AVERTISSEMENT



Des roues ou des tiges de soupape de gonflage de pneus inappropriées peuvent interférer avec les freins à disque pneumatique et causer un dégonflage rapide des pneus, des dommages aux composantes, une perte de contrôle du véhicule, des dommages aux propriétés ou des blessures graves.

Utilisez des roues ou tiges de soupape de gonflage de pneus procurant une liberté de roulement adéquate avec les freins à disque pneumatique dont cette suspension est équipée.

Contactez le fabricant du véhicule afin de déterminer le remplacement approprié de roues ou tiges de soupape de gonflage de pneus.

Trailer Commercial Vehicle Systems

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.(RIDEAIR) 743.3247
330.489.0045
Fax 800.696.4416

 **HENDRICKSON**[®]

www.hendrickson-intl.com

Hendrickson Canada

250 Chrysler Drive, Unit #3
Brampton, ON L6S 6B6 Canada
800.668.5360
905.789.1030
Fax 905.789.1033

DECAL SPECIFICATIONS

The type of material and adhesive used to produce and apply a decal is determined by the printer according to the information listed on this page of the decal PDF file. Where applicable, a special adhesive may be specified in Table 1.

ACTUAL SIZE: W x H

Mounting Surface:

Special Instructions:

Width Constraint ¹	Height Constraint ¹	Exposure to Sunlight ²	Water Resistant ³	Water Proof ⁴	Special Adhesive ⁵	Paint Mask ⁶	Heat ⁷	Cold ⁸	Extreme Wind ⁹	Writable ¹⁰
^{1.} Relative to intended location, maximum or minimum size constraints must apply as listed. None if left blank. ^{2.} Must not fade when exposed to sunlight over life of decal. ^{3.} Be able to resist rain water and hold position. Usually mounted vertically or at an incline such that water easily runs off. ^{4.} Able to hold position and not degrade when submersed or hold standing water. ^{5.} Applies to soft coated suspension components and where ever applicable, when checked. X = adhesive specified in Table 2 . ^{6.} Covered with a removable mask. The mask should include a pull tab for ease of removal after painting. ^{7.} Remain in tact and not fade or degrade in temperatures to HHH° (enter value). ^{8.} Hold position at temperatures below -LLL° (enter value). ^{9.} An example of this would be a hubcap decal that is exposed to spinning and exposure to the wind and any particles carried within it. ^{10.} Must be able to write on decal with permanent marker or ball point pen.										

Table 1: *Decal specifications*

SPECIAL ADHESIVES

The following are preferred adhesives for Hendrickson Trailer decals to be attached to soft coated and other suspension structural components. They have been tested with favorable results in Hendrickson Trailer applications. Hendrickson must be contacted prior to using other adhesive types in these applications.

Property	Fasson® TL2	P1480
Manufacture	Fasson	3M
Manufacture web site	www.na.fasson.com	www.3m.com
Adhesive type	Hot melt rubber	High performance tackified acrylic
Minimum application temperature	35° F (2° C)	40° F to 120° F (5°C to 49° C)
Service temperature range	-65° F to 150° F (-54°C to 65.5° C)	-20° F to 140° F (-29°C to 60° C)

Table 2: *Hendrickson approved decal adhesives*