

H HT™ SERIES

HT250US SPECIFICATIONS

LIT NO: L554

DATE: February 2020

REVISION: F





APPLICATIONS		
CAPACITY¹	25,000 lbs. (11 300 kg)	
TRAILER TYPES	UNITED STATES AND CANADA Drop Deck Van Auto Hauler Flat Lowboy / Drop Deck Dump Grain Livestock	MEXICO, CENTRAL AND SOUTH AMERICA None
AXLE DATA	5-inch diameter round, 5/8-inch min. wall ² , 12.25-inch, 15-inch or 16.5-inch drum brakes	
AXLE ARRANGEMENT	Single, tandem (up to 122-inch max. axle spacing), tri or quad axle	
FRAME TYPES	Steel or aluminum	
BASE MODEL DESCRIPTION:	HT™ Series underslung suspension, standard travel, weld-on wingless frame brackets with QUIK-ALIGN® and forward mount standard shocks.	
OTHER OPTIONS:	Additional options include limited jounce and extended rebound travel, high control, bolt-on frame brackets, shock straps, remote shock mounting and extreme service/high damping shocks. Contact your Hendrickson representative to discuss these and other product options.	

SPECIFICATIONS

SUSPENSION — HT250US (BASE MODELS ³)			
RIDE HEIGHT (inches)	JOUNCE ^{4,5} (inches)	REBOUND ^{4,5} (inches)	WEIGHT ⁶ (pounds)
3.5	2.6	3.0	327
4.0	3.1	3.2	327
5.5	2.1	4.7	361
6.5	3.1	3.7	361
7.5	3.2	6.3	378
9.0	4.7	4.8	378
12.0	5.3	4.3	393
14.0	5.3	4.3	407

- Capacity refers to suspension only rating. Ratings for axle, brakes and wheel-end components differ depending upon options chosen.
- Refer to Hendrickson's literature L980 for Hendrickson axle capacity rating recommendations. A thicker axle wall should be considered in more demanding applications.
- Other models and options are available.
- Jounce rebound and weight figures shown are for models with standard weld-on hangers and standard shock absorbers. These values differ slightly for other models and options. Contact Hendrickson for more information.
- Limited axle travel configurations and extended rebound 6.5-inch ride height models are also available.
- Weight shown does not include the axle.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS
2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada ULC
2825 Argenta Road, Unit #2 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.802.9423

Hendrickson Mexicana
Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601