

HENDRICKSON USE ONLY

Kit Part No.:

Kit Price:

ORDERING GUIDE
TIREMAAX® TIRE INFLATION SYSTEM

LIT NO: L868

DATE: December 2023

REVISION: S

FORM INSTRUCTIONS

For complete price and model number information for a TIREMAAX® system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		FROM:		COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:		

SAME AS:	EXCEPT:
-----------------	----------------

TIREMAAX®*(Continued on page 2)*

MODEL TYPE:	<input type="checkbox"/> CP	<input type="checkbox"/> PRO	<input type="checkbox"/> PRO-LB		
SUSPENSION CATEGORY: (PRO-LB is limited to suspension models shown)	N/A		<input type="checkbox"/> A	<input type="checkbox"/> B	<input type="checkbox"/> C
			VANTRAAX® HKANT 40K (≥16" RH) ULTRAA-K® UTKNT 40K	VANTRAAX HKANT 23K HKANT 40K (15" RH) HKANT / HKAT 46K INTRAAX® AANT / AAT 23K (≥13.5" RH, Std A/S Pressure) AANL / AAL 23K (Std A/S Pressure)	VANTRAAX HKAT 50K INTRAAX AANT / AAT 23K (≥13.5" RH, Low A/S Pressure) AANL / AAL 23K (Low A/S Pressure) AAT 25K AAL 25K AANLS 20K
ELECTRICAL CONNECTION:	<input type="checkbox"/> Delphi Weather Pack (Standard)		<input type="checkbox"/> Blade Terminals ¹		
KIT STYLE:	<input type="checkbox"/> For OEM Installation		<input type="checkbox"/> For Aftermarket / Retrofit Installation		

1. Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".

MODEL TYPE:	CP / PRO				PRO-LB				
TIRE SIZE:	<input type="checkbox"/> 17.5"	<input type="checkbox"/> 19.5"	<input type="checkbox"/> 22.5"	<input type="checkbox"/> 24.5"	<input type="checkbox"/> 22.5"	<input type="checkbox"/> 24.5"			
NUMBER OF AXLES:	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 1	<input type="checkbox"/> 2			
AXLE STYLE:	<input type="checkbox"/> Integrated (INTRAAX®, VANTRAAX®, ULTRAA-K®) <input type="checkbox"/> Standard (TRLAXLE®) Standard Axle Track: <input type="checkbox"/> 71.5" to 83" <input type="checkbox"/> 83.5" to 92"				<input type="checkbox"/> Integrated (INTRAAX, VANTRAAX, ULTRAA-K)				
AXLE PREPARATION:	<input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Hendrickson (Kit includes controller and tire hoses) <input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Trailer OEM (Kit includes controller, hubcap assemblies and tire hoses) <input type="checkbox"/> Not Prepped for TIREMAAX; Select Aftermarket / Retrofit kit style above (Kit includes controller, hubcap assemblies, tire hoses and axle kit)								
SPINDLE STYLE:	<input type="checkbox"/> HN <input type="checkbox"/> HP								
HUBCAP TYPE:	<input type="checkbox"/> Hendrickson Bolt-On <input type="checkbox"/> Hendrickson Extended Bolt-On ²								
LUBE TYPE:	<input type="checkbox"/> Semi-Fluid Grease <input type="checkbox"/> Oil								
WHEEL STYLE / MATERIAL:	<input type="checkbox"/> Dual / Aluminum		<input type="checkbox"/> Dual / Steel or Combo		<input type="checkbox"/> Super Single / Aluminum (Straight hose)		<input type="checkbox"/> Super Single / Steel (Inboard valve stem; straight hose)		
	<input type="checkbox"/> Super Single / Steel (Outboard valve stem; 180-degree hose)								
MODEL TYPE:	CP		PRO		PRO-LB				
COLD TIRE PRESSURE SETTING (PSI):	<input type="checkbox"/> 70	<input type="checkbox"/> 100	<input type="checkbox"/> 85	<input type="checkbox"/> 105	COLD TIRE PRESSURE SETTING (PSI) AT 17,000 LB:	Dual (Min. PSI = 75)		Super Single (Min. PSI = 90)	
	<input type="checkbox"/> 75	<input type="checkbox"/> 105	<input type="checkbox"/> 90	<input type="checkbox"/> 110		<input type="checkbox"/> 85	<input type="checkbox"/> 105	<input type="checkbox"/> 100	<input type="checkbox"/> 115*
	<input type="checkbox"/> 80	<input type="checkbox"/> 110	<input type="checkbox"/> 95	<input type="checkbox"/> 115		<input type="checkbox"/> 90	<input type="checkbox"/> 110*	<input type="checkbox"/> 105	<input type="checkbox"/> 120*
	<input type="checkbox"/> 85	<input type="checkbox"/> 115	<input type="checkbox"/> 100	<input type="checkbox"/> 120		<input type="checkbox"/> 95	<input type="checkbox"/> 115*	<input type="checkbox"/> 110*	
	<input type="checkbox"/> 90	<input type="checkbox"/> 120				<input type="checkbox"/> 100	<input type="checkbox"/> 120*		
	<input type="checkbox"/> 95								
TIRE HOSE:	<input type="checkbox"/> Standard <input type="checkbox"/> Integral Check Port (22.5" tire size only)								
INDICATOR LIGHT KIT:	<input type="checkbox"/> LED – 12V with 65-Foot Cable (Standard)		<input type="checkbox"/> LED – 12V with 35-Foot Cable		<input type="checkbox"/> LED – 24V with 65-Foot Cable (Export ³)				
	<input type="checkbox"/> No ¹								
WIRING HARNESS:	<input type="checkbox"/> Premium, 15-Foot, ABS-ready		<input type="checkbox"/> Premium, 3-Foot, ABS-ready		<input type="checkbox"/> Standard, 18-inch, Wiring Adapter Plug		<input type="checkbox"/> No ¹		
AIR PLUMBING KIT:	<input type="checkbox"/> Manifold ⁴ <input type="checkbox"/> No								
CONTROLLER TANK VALVE:	<input type="checkbox"/> Yes (CP models only) <input type="checkbox"/> No								

1. Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".

2. Required for axles with TIREMAAX PRO or PRO-LB equipped with cross-drilled spindles and using the castellated spindle nut. Please verify spindle nut requirements.

3. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

4. Not available for single-axle systems.

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.
All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.
Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada ULC

2825 Argentia Road, Unit #2 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.812.9423

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601