

HHT™ **SERIES**

HT250T SPECIFICATIONS

LIT NO: L223

DATE: January 2022

REVISION: E



HT250T SPECIFICATIONS



HT250T

*CAPACITY:	25,000 lbs. (11 250 kg)	
TRAILER TYPES:	UNITED STATES AND CANADA Platform Specialty Grain Livestock	MEXICO, CENTRAL AND SOUTH AMERICA None
**AXLE DATA:	5-inch diameter round, 5/8-inch wall, 15- and 16.5-inch brakes	
AXLE ARRANGEMENT:	Single; tandem: 122-inch maximum axle spacing Tri- or quad: 144-inch maximum total spacing	
FRAME TYPES:	Steel or aluminum; 96-inch or 102-inch wide trailers	
BASE MODEL DESCRIPTION:	HT® Series top-mount suspension, 15-inch ride height, weld-on, wingless frame brackets with QUIK-ALIGN® and rear mount shocks standard.	
***BASE MODEL WEIGHT:	341 lbs.	
OTHER OPTIONS:	Additional options include winged and bolt-on frame brackets and remote mount shock absorbers. Lift axle options also available. Contact your Hendrickson representative to discuss these and other product options such as pre-torqued pivot bolts and glove style bushing tube spacers.	

* Capacity refers to suspension ratings, except where noted. Ratings for brakes and wheel-end components differ depending upon options chosen. Can be used in place of HT230 suspensions or in conjunction with certain other suspensions when used as a lifttable.

** Hendrickson recommends 5/8-inch nominal wall thickness.

*** Weight shown does not include the axle or the frame bracket crossmember.

SPECIFICATIONS

SUSPENSION — HT250T		
RIDE HEIGHT (inches)	JOUNCE (inches)	REBOUND (inches)
12	4.0	5.2
14	6.0	3.2
15	6.5	3.0
16	6.1	3.0
17	6.5	3.0
19	6.0	2.9

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS
2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada ULC
2825 Argenta Road, Unit #2 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.802.9423

Hendrickson Mexicana
Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601