HVANTRAAX / ULTRAA-K Air Slider Suspension Systems

- Maximized payloads
- Superior performance
- Reduced maintenance





To learn more about VANTRAAX and ULTRAA-K, call 866.743.3247 or visit www.hendrickson-intl.com



The World Rides On Us®

HFamily of low-maintenance

ULTRAA-K®

Hendrickson introduces the latest in air slider technology with ULTRAA-K® axle suspension system – the next generation VANTRAAX® air slider system for the van and refrigerated trailer markets. Building on proven VANTRAAX air slider design expertise, the ULTRAA-K system is engineered with an optimized strength-to-weight ratio making it stronger and lighter than comparable standard and heavy-duty 40K slider models in the market today.

The ULTRAA-K system is standard with industry-exclusive and patented features such as ZMD® shockless ride technology, pivoting mud flap brackets and protected height control valve mounting.





HKANT 40K

Optimized for dry-freight and refrigerated sliding tandems, VANTRAAX HKANT 40K, with a capacity rating of 40,000 pounds, remains one of the lightest air suspension systems on the market. The patented QUIK-DRAW® pin activation system helps protect both drivers and payload. At the same time, it addresses critical needs for a superb ride, rugged durability and low maintenance.

Featuring the LDA[™] Large-Diameter Axle for increased roll stiffness, reduced weight and improved durability, the HKANT 40K helps haulers boost payloads and enhance fuel efficiency. ZMD shockless ride technology is available as an option on the HKANT 40K model.

HKANT 46K

This lightweight, tapered-beam, 46,000-pound capacity system features LDA axles and is tailor-made for haulers running heavy-duty, over-the-road box and refrigerated vans. The VANTRAAX HKANT 46K incorporates our patented QUIK-DRAW pin activation system, high-strength main rails and "K" braces for superior durability and frame strength. The close-spaced model is lighter than similar 46K systems.





HKANT 46K Wide spread

HKANT 46K – Wide Spread

A 121-inch spread configuration, the VANTRAAX 46K Wide Spread has the same features as the close-spaced 46K while providing load distribution flexibility and weight savings compared to equivalent models.

HKANT 23K

This 23,000-pound capacity system provides flexibility in axle spacing, allowing for increased carrying capacity and enhanced load distribution. The VANTRAAX HKANT 23K comes standard with QUIK-DRAW pin activation system and features the LDA axle for lighter weight and improved durability.



air slider suspension systems

HKAT 50K

With a capacity of 50,000 pounds, this rugged, durable VANTRAAX model featuring the LDA[™] axle proves ideal for haulers carrying heavier loads or running on secondary and unpaved highways.





HKAT 69K25 Tridem

HKANT 69K Tridem

Hendrickson's VANTRAAX® tridem sliders provide an ideal solution for haulers moving freight across North America. Tridems give operators the flexibility to haul across international, provincial and state borders, helping them remain compliant with a wide variety of bridge weight laws and Canadian "infrastructure-friendly" regulations. The VANTRAAX HKANT 69K23 and HKAT 69K25 models feature an overall system capacity of 69,000 pounds and axle ratings of 23,000 and 25,000 pounds, respectively.

VANTRAAX tridem sliders feature the LDA Large-Diameter Axle for increased roll stiffness, reduced weight and improved durability, helping haulers boost payloads and enhance fuel efficiency.

HKANL 23K - Liftable Single-Axle Slider

This liftable 23,000-pound capacity single-axle air slider system features LDA. This product has been specially designed with a larger amount of suspension up travel to provide increased suspension lift. The HKANL 23K can be useful in applications where one or two lift axles are used with a "standard travel" fixed or sliding tandem arrangement. In addition, this system provides flexibility in axle spacing, allowing for increased carrying capacity and enhanced load distribution. It comes standard with QUIK-DRAW® pin activation system, offering additional weight savings compared to similar models.





HKARL 46K Ramp-Ready

Eliminating heavy, expensive spacer tubes, the Ramp-Ready VANTRAAX delivers competitive advantages, cutting-edge technology and weight savings of an advanced system. With a capacity of 46,000 pounds, VANTRAAX Ramp-Ready features Hendrickson's LDA and a 6.5- by 30-inch ramp bay and installs on applicable trailers using industry-standard body rails with four- or six-inch pinhole spacing.

HKAL 46K

Ideal for drop-frame van applications, VANTRAAX HKAL 46K is standard with Hendrickson's LDA. It provides fleets and owner-operators with a lighter, more durable product that helps reduce operating costs over the long run.



Weigh the advantages of VANTRAAX® / ULTRAA-K®

Superior Axle Design



- LDA[™] Large-Diameter Axles featured on most INTRAAX® and VANTRAAX® suspension systems
 - Lighter than comparable industry standard 5 inch axles, allowing more cargo per load
 - Bending and torsional stiffness increased for reduced deflection
- Straighter, neutral-toe axle helps improve tire life and fuel mileage
- Advanced axle wrap and window weld technology for optimal structural integrity
- Spindle, axle wrap and spider mounting surfaces machined in one step after friction welding to ensure precise brake geometry and wheel positioning — for enhanced brake life and efficiency
- Brake hardware attached to trailing arms rather than welded to axle, minimizing axle stress
- Patented axle filter prevents wheel-end contamination




- Patented "K" bracing absorbs road jolts
- Superior strength-to-weight ratio for longer life
- Slides easily on durable, full-length slider pads


Low Maintenance and Convenience — **Help Save Time and Money**

- Simple, functional design uses fewer parts — that means fewer parts to maintain
- QUIK-ALIGN® Pivot Connection fast and easy axle realignment requires no welding or special tools
- TRI-FUNCTIONAL® Bushings proven technology for mile after mile of dependable service
- Single source for comprehensive technical support, training and warranty

Responsive and Consistent Stopping Power

- Hendrickson's standard Cam Tube System[™] enhances S-cam alignment and helps extend brake component life
 - Superior grease volume compared to spherical-style camshaft assemblies
- 10-inch S-cam eliminates windup and reduces bushing wear
 - Up to a half-inch less stroke required





- Faster application and release cycles
- Heat-treated components for greater durability

Performance Plus

- Low spring rates deliver superb ride quality
- Optional high-capacity air springs allow rapid air-up
- Rigid trailing arm with solid axle connection offers stable and durable design
- TRI-FUNCTIONAL® Bushings optimize ride softness and control
- Quality-controlled assembly, including ABS sensor testing ensures optimal performance

Low-Maintenance Integrated Systems from a Single Source

- Long-term warranty on axle / beam connection*
- Leading structural warranty*
- Supported by OEMs, dealers and designated distributors throughout North America
- Backed by Hendrickson's outstanding technical support staff
- Quickly replace damaged axles without grinding or welding
- · Wide availability of Hendrickson Genuine Parts
- * Applicable for most geographic areas and applications. Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.






HENDRICKS

VANTRAAX® / ULTRAA-K® Air Slider Suspension Systems

ZMD® ZERO MAINTENANCE DAMPING®

Hendrickson's ZERO MAINTENANCE DAMPING® exclusive ride technology

- Reduces suspension maintenance by eliminating shocks
- Uniform damping levels
- Superior driver comfort, ride quality and cargo protection
- Robust chain down stop provides maximum durability
- Standard on ULTRAA-K[®] and available as an option on select VANTRAAX[®] models





Hendrickson-Installed UBL™ UNDER BEAM LIFT™*

Lightweight lift axle mechanism


- Operational flexibility
- Improved maneuverability
- Maximized payloads See UBL flyer L727
 *Not available on ULTRAA-K®

TIREMAAX®

Advanced tire pressure control systems

- Automatically inflates, relieves, equalizes and adjusts trailer tire pressures
- Helps fleets improve fuel economy, tire life and operational uptime
- TIREMAAX® PRO-LB empowers fleets to maximize tire life and uptime with load-based adjustments

See TIREMAAX PRO-LB flyer - L1333



WATCHMAN®

Wheel-end sensor technology

- Available on suspension models that specify TIREMAAX PRO or TIREMAAX PRO-LB tire pressure control systems
- Constantly monitors trailer tire pressures for pre-trip confidence
- Provides real-time alerts to the fleet's back office when a potential issue is detected
- Helps accelerate issue resolution and maximize uptime when employed as part of a fleet's proactive maintenance routine

Loading Dock Solutions

For more efficient loading and unloading

SURELOK® Ride Height Lock Mechanism

- Maintains trailer deck height
- Limits trailer drop and walk
- Activates automatically with trailer parking brakes

DST® Dock Stabilizing Technology™

- Minimizes trailer walk
- Patented integral height control/dump valve exhausts twice as fast as conventional valves
- Activates automatically with trailer parking brakes
- · Supports load on internal air spring bumpers

Manual and automatic dump valves

- Limit trailer drop and walk
- · Support load on internal air spring bumpers

See SURELOK flyer - L622 See Trailer Loading Dock Terms and Solutions - L816

OUIK-DRAW®

Fully pneumatic slider pin system

- Driver-friendly finger-tip operation
- Helps reduce driver strain and enhance productivity
- Automatic reset engages pins when parking brake releases
 See QUIK-DRAW flyer L628



Brake Options

Extend intervals between brake service

- HXS® Hendrickson Extended Service™ brakes, with thicker lining blocks, work to extend brake life
- Wide HXS (16.5- x 8.625-inch) brakes can help increase the miles between lining changes
- Air disc brakes available

See Understanding Air Suspensions - (Brake Efficiency) - L761 See Air Disc Brake flyer - L889

RTR® READY-TO-ROLL®

Fully integrated solutions that help minimize operating costs and improve performance

- Suspension through wheel-end systems deliver low maintenance, improved durability and reduced weight with the convenience of a single-source supplier
 - HXL3® Hendrickson Extended-Life 3-year System™*
 - HXL5® Hendrickson Extended-Life 5-year System™*
 - HXL7® Hendrickson Extended-Life 7-year System™*

See RTR READY-TO-ROLL Wheel-End flyer - L1200

Corrosion Protection / Coatings

Hendrickson coating options help protect your investment

- Hot Dip Wax: Exclusive to ULTRAA-K, a self-healing, pliable coating that has the ability to re-seal itself in areas with minimal damage. Entire slider box is coated for exceptional coverage and comes with a 10-year structural corrosion warranty*
- Black Soft-Coat: A self-healing, pliable, water-resistant coating that has the ability to re-seal itself in areas with minimal damage
- Hot-Dipped Galvanized: Zinc coating for improved chip and corrosion resistance. Available on select VANTRAAX and ULTRAA-K slider boxes
- Black Primer: Uses a multi-stage cleaning and preparation process for high adhesion
- E-coat: All Hendrickson brake shoes are standard with high quality, e-coat for improved resistance to rust-jacking
- AAXTREME COAT®: All Hendrickson brake shoe coating provides superior corrosion protection in tough environments

See E-coat brochure - L1205 See AAXTREME COAT flyer - L1207

Hendrickson MAXX22T™

Optimized trailer air disc brake system

- Proprietary Hendrickson MAXX22T brake caliper
- Lightweight rotor and torque plate deliver substantial weight savings over standard ductile iron designs
- Bolt-on dust shield for easier installation and maintenance
- Hendrickson comprehensive warranty* coverage
- Available with outboard mounted rotor technology for enhanced serviceability

See MAXX22T brochure - L1239



^{*}Contact your local Hendrickson representative or see L583 Comprehensive Warranty Statement for complete warranty terms, conditions and limitations.

VANTRAAX® / ULTRAA-K® Built to last



VANTRAAX® and ULTRAA-K® address the industry's need for lighter, more durable products that help reduce operating costs. Fleet owners and owner-operators insist on Hendrickson slider systems for their dry-freight and refrigerated vans to take advantage of superior performance, added payload and enhanced cargo protection.

VANTRAAX marries our superior K-2® slider box technology with the patented INTRAAX® integrated suspension / axle / brake system recognized industry-wide for its durable performance and lightweight design. This winning combination of legendary durability and road-proven reliability contributes to the enduring value of VANTRAAX.

The VANTRAAX family has grown to include a variety of slider models to cover a range of North American trailer applications and operating conditions. Close-spaced tandems in top-mount and low-ride configurations, as well as tridems in wide-spread configurations, provide the product depth you have come to expect from Hendrickson.

The latest innovation in trailer air slider systems is ULTRAA-K – the next-generation VANTRAAX air slider suspension system. Building on the proven VANTRAAX design, ULTRAA-K is engineered with an optimized strength-to-weight ratio making it stronger and nearly 100 pounds lighter than comparable air slider suspension systems. ULTRAA-K is an elite system that features exclusive and patented Hendrickson technology.

VANTRAAX / ULTRAA-K Specifications

Model	Axle Arrangement	Axle Spacing (in.)	System Capacity (lb.)	Axle Rating (lb.)	Axle Diameter	Box Width (in.)	Ride Height (in.)*	Base Model Weight (lb.)**
ULTRAA-K	Tandem	49	40,000	20,000	LDA™	48	16	1,294
HKANT 23K	Single	N/A	23,000	23,000	LDA	42, 48	16, 17	785
HKANT 40K	Tandem	49	40,000	20,000	LDA	42, 48	16, 17	1,394
HKANT 46K	Tandem	49, 121	46,000	23,000	LDA	42^, 48	16, 17	1,405
HKAT 50K	Tandem	49	50,000	25,000	LDA	42, 48	16, 17, 18, 19	1,579
HKANT 69K23	Tridem	49, 60, 72	69,000	23,000	LDA	48	16, 16.5, 17, 18	2,236
HKAT 69K25	Tridem	60, 72	69,000	25,000	LDA	42, 48	16, 17, 18	2,479
HKANL 23K	Single	N/A	23,000	23,000	LDA	42, 48	17	857
HKAL 46K	Tandem	49	46,000	23,000	LDA	42, 48	10, 11	1,670
HKARL 46K	Tandem	49	46,000	23,000	LDA	48	10, 11	1,840

^{*} Contact Hendrickson for non-standard ride height availability.

These products are covered by at least one or more U.S. and/or foreign patents and/or pending U.S. and/or foreign patent applications. See Hendrickson for details.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS 2070 Industrial Place SE

Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) Fax 800.696.4416 Hendrickson Canada ULC 2825 Argentia Road, Unit #2 - 4 Mississauga, ON Canada L5N 8G6 800.668.5360 905.789.1030 • Fax 905.812.9423

4 Circ 8G6 Pard Pob. 423 Que

Hendrickson Mexicana Circuito El Marqués Sur #29 Parque Industrial El Marqués Pob. El Colorado, Municipio El Marqués, Querétaro, México C.P. 76246 +52 (442) 296.3600 • Fax +52 (442) 296.3601

^{**} Weights include slider, suspensions, HN spindles and foundation brakes for 48-inch wide slider box. Tandem weights are based on 49-inch axle spacing.

Tridem weights are based on 72-inch axle spacing. ULTRAA-K weight does not include pivoting mud flap brackets, HCV kit or air tank brackets.

Not available on 121-inch axle spread model.