

HHT™ **SERIES**

HT300YB Y-BEAM SPECIFICATIONS

LIT NO: L1187

DATE: March 2011





APPLICATIONS

CAPACITY*:	HT300YB - 30,000 lbs. (13 600 kg)
TRAILER TYPES:	U.S.A. and Canada: Lowboy / Drop Deck, Specialty Trailers Mexico, Central and South America: None
AXLE DATA:	5-inch diameter round, 5/8-inch wall, S-cam, w/ or w/o auto slack adjusters for 15-, 20-, or 22-inch wheels Brake size: 12.25 or 16.50 inch
AXLE ARRANGEMENT:	Single, tandem: 122-inch maximum axle spacing Tri or quad: 144-inch maximum total spacing
FRAME TYPES:	Steel; 96-inch or 102-inch wide trailers

* Capacity refers to the suspension ratings. Ratings for the axle, brakes and wheel-end components differ depending upon their specifications

SPECIFICATIONS

Suspension Model Number	Ride Height (inches)	Jounce (inches)	Rebound (inches)	Weight (lbs.) ¹	Compatible Trailing Suspension
HT300UB7.5-001	7.5	3.3	5.4	446	HT300UB6.5-001
HT300YB-9-001	9	4.2	5.4	446	HT300UB9-001

All models for the HT300YB feature the QUIK-ALIGN® pivot connection.

Options available for HT300YB

Shock straps²

1. Weights shown above are for standard models (standard air spring and shock) and do not include axle
2. Shock strap kit must be ordered separately from suspension — contact Hendrickson for proper kit

SUSPENSION APPLICATION NOTE:

Care must be taken to insure that any additional suspensions used on the same vehicle are compatible with the Y-beam suspension. For assistance, please contact your Hendrickson Trailer Suspension Systems customer service representative.

www.hendrickson-intl.com



Trailer Suspension Systems
250 Chrysler Drive, Unit #3
Brampton, ON Canada L6S 6B6
905.789.1030
Fax 905.789.1033

Trailer Suspension Systems 866.RIDEAIR (743.3247)
2070 Industrial Place SE 330.489.0045
Canton, OH 44707-2641 USA Fax 800.696.4416

Hendrickson Mexicana
Av. Industria Automotriz #200
Parque Industrial Sliva Aeropuerto
Apodaca, N.L., México C.P. 66600
+52 (81) 8288.1300
Fax +52 (81) 8288.1301