

**HENDRICKSON USE ONLY**

# **ORDERING GUIDE**

## **HT™ SERIES 25K/30K UNDERSLUNG and Y-BEAM SUSPENSIONS**

LIT NO: L555

DATE: August 2019

REVISION: J

### **FORM INSTRUCTIONS**

For complete price and model number information on an HT250US, HT300US or HT300YB suspension, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

<b>TO:</b>	<b>FROM:</b>	<b>COMPANY NAME:</b>	
<b>DATE:</b>	<b>PHONE:</b>	<b>FAX:</b>	<b>EMAIL:</b>

<b>SAME AS:</b>	<b>EXCEPT:</b>
-----------------	----------------

### **SUSPENSION**

<b>SUSPENSION MODEL</b> (capacity):	<input type="checkbox"/> HT250US (25K)	<input type="checkbox"/> HT300US (30K)				
<b>AXLE CONNECTION:</b>	None					
<b>RIDE HEIGHT</b> (inches):	<input type="checkbox"/> 3.5" (25K only) <input type="checkbox"/> 12"	<input type="checkbox"/> 4" (25K only) <input type="checkbox"/> 14"	<input type="checkbox"/> 5.5" <input type="checkbox"/> 17" (30K only)	<input type="checkbox"/> 6.5"	<input type="checkbox"/> 7.5"	<input type="checkbox"/> 9"
<b>TRAVEL:</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> Limited Jounce	<input type="checkbox"/> Extended Rebound			
<b>FRAME ATTACHMENT:</b>	<input type="checkbox"/> Weld-On	<input type="checkbox"/> Bolt-On	<input type="checkbox"/> Other			
<b>AIR SPRING PSI RANGE:</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> High Pressure (25K only)				
<b>AIR SPRING MOUNTING PLATE:</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> Rotated (25K only)	<input type="checkbox"/> None			
<b>SHOCK ABSORBER:</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> Extended Service / High Damping <sup>1</sup>				
<b>SHOCK MOUNTING:</b>	<input type="checkbox"/> Forward Upper Mount (Standard)	<input type="checkbox"/> Remote Mount				
<b>SHOCK STRAPS:</b>	<input type="checkbox"/> Yes	<input type="checkbox"/> No				
<b>FRAME BRACKET TO BEAM:</b>	<input type="checkbox"/> Assembled	<input type="checkbox"/> Non-Assembled				
<b>TIRE SIZE</b> (inches): (To determine U-bolt)	<input type="checkbox"/> 17.5" (25K only)	<input type="checkbox"/> 19.5" or larger				
<b>FRAME BRACKET SUPPORT</b> (C-Channel):	<input type="checkbox"/> Weld-on C-Channel	<input type="checkbox"/> Customer Supplied				
<b>HIGH CONTROL SUSPENSION<sup>2</sup>:</b>	<input type="checkbox"/> Yes	<input type="checkbox"/> No				
<b>AXLE STYLE:</b>	<input type="checkbox"/> Standard	<input type="checkbox"/> Steerable (25K only)				
<b>BRAKE TYPE:</b>	Drum Only (Air disc brakes not available)					
<b>BEAM COATING</b> (Suspension Coating):	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None				
<b>FRAME COMPONENTS COATING:</b> (Frame Bracket Coating)	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None / Do not paint frame brackets				



Are you ordering a Y-Beam suspension?  No  Yes (continue to page 2)

1. Required for HT300US suspension.
2. High control suspensions are recommended for single-axle trailers in multi-trailer combinations, all dollies and full trailers with two single axles. Not for use on multiple-axle trailers.

NOTE: Some combinations may not be compatible or available.

 **HENDRICKSON**

## SUSPENSION

<b>SUSPENSION MODEL</b> (capacity):	<input type="checkbox"/> HT300YB <sup>3</sup> (30K Y-Beam)
<b>AXLE CONNECTION:</b>	None
<b>RIDE HEIGHT</b> (inches):	<input type="checkbox"/> 6.5" <input type="checkbox"/> 7.5" <input type="checkbox"/> 9"
<b>TRAVEL:</b>	Standard
<b>FRAME ATTACHMENT:</b>	Y-Beam
<b>AIR SPRING PSI RANGE:</b>	Standard
<b>AIR SPRING MOUNTING PLATE:</b>	<input type="checkbox"/> Standard <input type="checkbox"/> None
<b>SHOCK ABSORBER:</b>	Standard
<b>SHOCK MOUNTING:</b>	Forward Upper Mount (Standard)
<b>SHOCK STRAPS:</b>	<input type="checkbox"/> Yes <input type="checkbox"/> No
<b>FRAME BRACKET TO BEAM:</b>	Non-Assembled
<b>TIRE SIZE</b> (inches):	19.5" or larger
<b>FRAME BRACKET SUPPORT</b> (C-Channel):	None (Y-Beam)
<b>HIGH CONTROL SUSPENSION:</b>	No
<b>AXLE STYLE:</b>	Standard
<b>BRAKE TYPE:</b>	Drum Only (Air disc brakes are not available)
<b>BEAM COATING</b> (Suspension Coating):	<input type="checkbox"/> Standard Black Primer <input type="checkbox"/> None
<b>FRAME COMPONENTS COATING:</b> (Frame Bracket Coating)	None

3. For use in conjunction with HT300US suspensions.

*Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.  
All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.  
Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.*

Call Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

L964 Rev J 08-19

© 2007 - 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

### TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

### Hendrickson Canada

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

### Hendrickson Mexicana

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601