

# **H**HT™ **SERIES**

## **HT300T SPECIFICATIONS**

LIT NO: L90

DATE: May 2014

REVISION: E

---





APPLICATIONS																					
<b>*CAPACITY:</b>	30,000 lbs. (13 600 kg)																				
<b>TRAILER TYPES:</b>	<table border="1"> <thead> <tr> <th>UNITED STATES AND CANADA</th> <th>MEXICO, CENTRAL AND SOUTH AMERICA</th> </tr> </thead> <tbody> <tr> <td>Container Chassis</td> <td>Van</td> </tr> <tr> <td>Chip Van</td> <td>Dump</td> </tr> <tr> <td>Flat</td> <td>Tanker</td> </tr> <tr> <td>Dump</td> <td>Reefer</td> </tr> <tr> <td></td> <td>Container Chassis</td> </tr> <tr> <td></td> <td>Chip Van</td> </tr> <tr> <td></td> <td>Flat</td> </tr> <tr> <td></td> <td>Grain</td> </tr> <tr> <td></td> <td>Livestock</td> </tr> </tbody> </table>	UNITED STATES AND CANADA	MEXICO, CENTRAL AND SOUTH AMERICA	Container Chassis	Van	Chip Van	Dump	Flat	Tanker	Dump	Reefer		Container Chassis		Chip Van		Flat		Grain		Livestock
UNITED STATES AND CANADA	MEXICO, CENTRAL AND SOUTH AMERICA																				
Container Chassis	Van																				
Chip Van	Dump																				
Flat	Tanker																				
Dump	Reefer																				
	Container Chassis																				
	Chip Van																				
	Flat																				
	Grain																				
	Livestock																				
<b>AXLE DATA:</b>	5-inch diameter round, 5/8-inch wall, 15- and 16.5-inch brakes																				
<b>AXLE ARRANGEMENT:</b>	Single; tandem: 54-inch maximum axle spacing																				
<b>FRAME TYPES:</b>	Steel or aluminum; 96-inch or 102-inch wide trailers																				
<b>BASE MODEL DESCRIPTION:</b>	HT™ Series top-mount suspension, 15-inch ride height, weld-on, wingless frame brackets with QUIK-ALIGN®, glove style bushing tube spacers and heavy duty shocks standard.																				
<b>**BASE MODEL WEIGHT:</b>	346 lbs.																				
<b>OTHER OPTIONS:</b>	Additional options include winged and bolt-on frame brackets and remote mount shock absorbers. Lift axle options also available. Contact your Hendrickson representative to discuss these and other product options such as pre-torqued pivot bolts.																				

\* Capacity refers to suspension ratings, except where noted. Ratings for brakes and wheel-end components differ depending upon options chosen.

\*\* Weight shown does not include the axle or the frame bracket crossmember.

## SPECIFICATIONS

SUSPENSION — HT300T		
RIDE HEIGHT (inches)	JOUNCE (inches)	REBOUND (inches)
15	3.4	4.4
17	3.3	4.4
19	4.2	3.1
21	4.2	4.1
23	3.5	4.3

Call your trailer dealer or Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

### TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

### Hendrickson Canada

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

### Hendrickson Mexicana

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601