

**HENDRICKSON USE ONLY**

Kit Part No.:

Kit Price:

**H ORDERING GUIDE**  
**TIREMAAX® TIRE INFLATION SYSTEM**

LIT NO: L868

DATE: March 2017

REVISION: 0

**FORM INSTRUCTIONS**

For complete price and model number information for a TIREMAAX® system, fax this form to 800.696.4416 in the U.S. or 905.789.1033 in Canada. For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

<b>TO:</b>		<b>FROM:</b>		<b>COMPANY NAME:</b>	
<b>DATE:</b>	<b>PHONE:</b>	<b>FAX:</b>	<b>EMAIL:</b>		

<b>SAME AS:</b>	<b>EXCEPT:</b>
-----------------	----------------

**TIREMAAX®<sup>1</sup>** (Continued on page 2)

<b>CONTROLLER TYPE:</b>	<input type="checkbox"/> CP	<input type="checkbox"/> PRO
<b>ELECTRICAL CONNECTION:</b>	<input type="checkbox"/> Delphi Weather Pack (Standard)	<input type="checkbox"/> Blade Terminals <sup>2</sup> (Hendrickson Controls approval required)
<b>KIT STYLE:</b>	<input type="checkbox"/> For OEM Installation	<input type="checkbox"/> For Aftermarket / Retrofit Installation
<b>AXLE STYLE:</b>	<input type="checkbox"/> Integrated (INTRAAX®, VANTRAAX®, etc.)	
	<input type="checkbox"/> Standard (Hendrickson TRLAXLE®)	<b>Standard Axle Track:</b> <input type="checkbox"/> 71.5" to 83" <input type="checkbox"/> 83.5" to 92"
<b>AXLE PREPARATION:</b>	<input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Hendrickson (Kit includes controller and tire hoses only.) <input type="checkbox"/> TIREMAAX Prepped / Wheel-ends Installed by Trailer OEM (Kit includes controller, hubcap assemblies and tire hoses.) <input type="checkbox"/> Not Prepped for TIREMAAX (Select for Aftermarket / Retrofit applications; Kit includes controller, hubcap assemblies, tire hoses and axle kit.)	
<b>NUMBER OF AXLES:</b>	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> Other:	
<b>SPINDLE STYLE:</b>	<input type="checkbox"/> HN <input type="checkbox"/> HP	
<b>HUBCAP TYPE:</b>	<input type="checkbox"/> Hendrickson Bolt-On	<input type="checkbox"/> Hendrickson Extended Bolt-On <sup>3</sup>
<b>LUBE TYPE:</b>	<input type="checkbox"/> Semi-Fluid Grease <input type="checkbox"/> Oil	
<b>WHEEL STYLE / MATERIAL</b>	<input type="checkbox"/> Dual / Aluminum <input type="checkbox"/> Dual / Steel or Combo <input type="checkbox"/> Super Single / Aluminum (straight hose) <input type="checkbox"/> Super Single / Steel (outboard valve stem; 180-degree hose) <input type="checkbox"/> Super Single / Steel (inboard valve stem; straight hose)	
<b>TIRE SIZE:</b>	<input type="checkbox"/> 17.5" <input type="checkbox"/> 19.5" <input type="checkbox"/> 22.5" <input type="checkbox"/> 24.5"	
<b>COLD TIRE PRESSURE SETTING (psi)<sup>4</sup>:</b>	<input type="checkbox"/> 70 <input type="checkbox"/> 75 <input type="checkbox"/> 80 <input type="checkbox"/> 85 <input type="checkbox"/> 90 <input type="checkbox"/> 95 <input type="checkbox"/> 100 <input type="checkbox"/> 105 <input type="checkbox"/> 110 <input type="checkbox"/> 115 <input type="checkbox"/> 120	

- Hendrickson does not provide warranty coverage for the installation, performance or components of a competitor brand tire inflation system installed on a Hendrickson suspension or trailer axle. Any consequential damages to the Hendrickson suspension or trailer axle resulting from a failure to the competitor brand tire inflation system or components, whether installed by the OEM, repair facility or end-user customer, should be directed to the respective tire inflation system manufacturer for warranty coverage.
- Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".
- Required for axles with TIREMAAX PRO equipped with cross-drilled spindles and using the castellated spindle nut. Please verify spindle nut requirements.
- Refer to tire manufacturer's recommended tire pressure. TIREMAAX PRO is restricted to cold tire pressure setting of 85-120 psi.

**H HENDRICKSON**

**TIREMAAX®***(Continued from page 1)*

<b>TRAILER-MOUNTED INDICATOR LIGHT KIT:</b>	<input type="checkbox"/> LED – 12V with 65-foot Cable (Standard)	<input type="checkbox"/> LED – 12V with 35-foot Cable	<input type="checkbox"/> LED – 24V (Export <sup>5</sup> )
	<input type="checkbox"/> Incandescent – 12V	<input type="checkbox"/> No <sup>2</sup>	
<b>WIRING HARNESS:</b>	<input type="checkbox"/> Premium, 15-Foot, ABS-ready	<input type="checkbox"/> Premium, 3-Foot, ABS-ready	
	<input type="checkbox"/> Standard, 18-inch, Wiring Adapter Plug	<input type="checkbox"/> No <sup>2</sup> (Hendrickson Controls approval required)	
<b>AIR PLUMBING KIT:</b>	<input type="checkbox"/> Manifold <sup>6</sup>	<input type="checkbox"/> No	
<b>CONTROLLER TANK VALVE<sup>7</sup>:</b> (Pressure Check)	<input type="checkbox"/> Yes (CP Models Only)	<input type="checkbox"/> No	

5. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

6. Not available for single-axle systems.

7. Not available with TIREMAAX PRO.

Call your trailer dealer or Hendrickson at **330.489.0045** or **866.RIDEAIR (743.3247)** for additional information.



[www.hendrickson-intl.com](http://www.hendrickson-intl.com)

**TRAILER COMMERCIAL VEHICLE SYSTEMS**

2070 Industrial Place SE  
Canton, OH 44707-2641 USA  
866.RIDEAIR (743.3247)  
330.489.0045 • Fax 800.696.4416

**Hendrickson Canada**

250 Chrysler Drive, Unit #3  
Brampton, ON Canada L6S 6B6  
800.668.5360  
905.789.1030 • Fax 905.789.1033

**Hendrickson Mexicana**

Circuito El Marqués Sur #29  
Parque Industrial El Marqués  
Pob. El Colorado, Municipio El Marqués,  
Querétaro, México C.P. 76246  
+52 (442) 296.3600 • Fax +52 (442) 296.3601