


H LONG TRAVEL TRAILING ARM AIR SUSPENSION

- Maximize mobility
- Maximize ride quality
- Maximize reliability




To learn more about Military Suspension
Products, call 630.910.2800 or visit
www.hendrickson-defense.com

H **HENDRICKSON**
The World Rides On Us®

Long Travel Trailing Arm Suspension Features and Benefits

Hendrickson's Long Travel Trailing Arm Suspension is ideal for military and severe off-highway applications requiring superior wheel travel for outstanding maneuverability in harsh environments while protecting driver and vehicle equipment. Simplify vehicle integration with more weight savings, less system complexity and less maintenance over competitive independent suspensions at a fraction of the cost. This suspension allows a variety of packaging, ride heights, ride tuning and stability requirements for a fully customizable design to meet the stringent performance characteristics demanded by the military and commercial markets.



Trailing Arm and Frame Hanger

- Fabricated design made with high strength materials to handle treacherous environments to reach over 12 inches of wheel travel

Axle Connection

- Genuine Hendrickson axle connection rigorously tested for the military market
- Through bolt design fits most industry-standard military axles

Premium options available for full customization and optimal performance

TORQUE RODS

- V-Rod or Longitudinal / Transverse torque rods available for packaging variations



SHOCKS

- Various technologies and mounting solutions available to tailor damping characteristics and ride tuning

AIR SPRINGS

- Robust design allows exceptional wheel travel
- Large volume air springs provide low spring rates similar to independent suspensions to maximize ride quality
- Coil springs optional (*pictured at right*)



STABILIZERS

- Stabilizers available for added stability



HPAS™ COMPATIBLE

- Supplement for active ride height control and load leveling



Suspension capacity	27,000 lbs. per axle
Axle configurations	Single, tandem, tridem
Axle spacing	Up to 56 inches

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at **630.910.2800** or **855.RIDERED (743.3733)** for additional information.



TRUCK COMMERCIAL VEHICLE SYSTEMS
 800 South Frontage Road
 Woodridge, IL 60517-4904 USA
 855.RIDERED (743.3733)
 630.910.2800 • Fax 630.910.2899

www.hendrickson-defense.com

45745-474 Rev A 07-19

© 2017 – 2019 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries. Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America