

HENDRICKSON USE ONLY**H[®] ORDERING GUIDE**
ULTRAA-K[®] SLIDER SUSPENSION

LIT NO: L1226

DATE: January 2025

REVISION: U

FORM INSTRUCTIONS

For complete price and model number information on an ULTRAA-K[®] slider suspension system, email this form to the appropriate contact (see page 8). For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:		FROM:		COMPANY NAME:	
DATE:	PHONE:	FAX:		EMAIL:	

SAME AS:	EXCEPT:
-----------------	----------------

SLIDER / SUSPENSION	
AXLE ARRANGEMENT:	Tandem
RAMP-READY:	N/A
MODEL:	UTKNT 40K
BOX DUTY:	Standard
SUSPENSION DAMPING:	ZMD [®] Zero Maintenance Damping [®]
AXLE SPREAD:	49"
RIDE HEIGHT:	16"
BOX WIDTH / AXLE TRACK:	48" / 77.5"

SLIDER PIN EXTRACTOR:	☐ QUIK-DRAW [®]	☐ QUIK-DRAW / No Valve	☐ Fixed
BODY RAIL STYLE¹:	☐ 1.375" x 6" HC	☐ 1.625" x 4" HC	☐ 1.375" x 4" HC (TTMA)
SLIDER BOX SHIMS:	☐ None	☐ .18"	☐ .232"
SHOCK STRAPS:	N/A		
HCV PRE-INSTALLED:	☐ Standard	☐ Integral Dump	
	Fitting Type:	☐ Compression (Std.)	☐ Push-to-Connect
WALK / DROP SOLUTIONS:	☐ None	☐ SURELOK [®] Installed	☐ SURELOK Ready
SURELOK AIR KIT:	☐ N/A	☐ Manual Bypass	☐ Manual Bypass w/ Dump ☐ No Valve (Order separately)
SURFACE COATING:	☐ Hot Dip Wax	☐ Galvanized	
Slider Box			
Suspension	Finished Black Soft Coat	☐ Finished Black Soft Coat ☐ Black Primer	
AIR TANK BRACKET:	☐ Standard	☐ Short Bolt-On	

1. Information purposes only; Hendrickson does not supply body rails.

AXLE

SPINDLE:	☐ HN	☐ HP	☐ HX ²
TIRE INFLATION SYSTEM³:	☐ TIREMAAX [®] CP ⁴ (Complete Worksheet on page 8) ☐ TIREMAAX PRO (Complete Worksheet on page 8) ☐ 3-Hole Prep ☐ No		
	☐ TIREMAAX PRO-LB (Complete Worksheet on page 8)		



Are you ordering air disc brakes? ☐ No (Continue on page 2) ☐ Yes (Go to page 4)

DRUM BRAKES *

*Slack and brake chamber combinations will affect brake ratings. Refer to L809 for Brake Certifications.

BRAKE LINING:	☐ H20		☐ H23		☐ H26	
BRAKE SIZE:	☐ 16.5" x 7"	☐ 16.5" x 8-5/8"	☐ 16.5" x 7"	☐ 16.5" x 8-5/8"	☐ 16.5" x 7"	☐ 16.5" x 8-5/8"
BRAKE MODEL:	☐ Standard ☐ HXS [®]	HXS	HXS	HXS	HXS	HXS
BRAKE COATING:	☐ Standard ☐ AAXTREME COAT [®] (HXS Only)		☐ Standard ☐ AAXTREME COAT (HXS Only)		Standard	
BRAKE CHAMBERS⁵:	☐ None	☐ 2.5" Standard Stroke				☐ 3.0" Long Stroke
SIZE / WARRANTY:		☐ Type 30/30 Standard Warranty	☐ Type 30/30 Extended Warranty	☐ Type 24/30 Standard Warranty	☐ Type 24/24 Standard Warranty	☐ Type 30/30 Standard ☐ Type 30/30 Extended Warranty
SLACK ADJUSTER:	☐ None	☐ Standard 5.5"			☐ Standard 6.0"	
S-CAM:	☐ 28 Spline ☐ 10 Spline					
DUST SHIELD:	☐ No ☐ Yes					
ABS SENSOR:	☐ No	☐ Haldex 19.7"	☐ WABCO 15.7"	☐ Bendix 14.8"	☐ Bendix 78.7"	☐ WABCO 36.0"
ABS SENSOR LOCATION:	Single:	☐ None ☐ 2				
	Tandem:	☐ None	☐ 2 – Front	☐ 2 – Rear		☐ 4 – Both
	Tridem:	☐ None	☐ 2 – Front	☐ 2 – Middle		☐ 2 – Rear
		☐ 4 – Front and Middle	☐ 4 – Front and Rear	☐ 4 – Middle and Rear		☐ 6 – All
SPINDLE NUT:	☐ No ☐ Standard 3-Piece Nut					

2. HX Spindle is available with Outboard Mounted Rotor only.

3. Refer to Hendrickson publication L583 Comprehensive Warranty Statement for complete details related to competitor tire inflation systems.

4. Outboard Mounted Rotor is not available with TIREMAAX CP.

5. Unless otherwise indicated, standard brand will be provided.

DRUM BRAKE RTR® READY-TO-ROLL® PACKAGES *

*Consult a customer service representative to ensure compatibility of the wheel-end equipment with the other selected suspension parameters.

	☐ Standard Service (1-Year Limited Warranty ⁶)	☐ HXL3® Hendrickson Extended-Life System™ (3-Year Limited Warranty ⁶)	☐ HXL5® Hendrickson Extended-Life System™ (5-Year Limited Warranty ⁶)	☐ HXL7® Hendrickson Extended-Life System™ (7-Year Limited Warranty ⁶)	☐ ConMet PreSet® (5-Year Limited Warranty ⁶)
SPINDLE:	☐ HN ☐ HP	☐ HN ☐ HP	☐ HN ☐ HP	HP	☐ HN ☐ HP
HUB MATERIAL:	☐ Ductile Iron ☐ Dura-Light Hub® ☐ Aluminum	☐ Ductile Iron ☐ Dura-Light Hub ☐ Aluminum	☐ Ductile Iron ☐ Dura-Light Hub ☐ Aluminum	☐ Ductile Iron ☐ Dura-Light Hub ☐ Aluminum	Aluminum
HUB STYLE:	Hub Piloted	Hub Piloted	Hub Piloted	Hub Piloted	Hub Piloted
NUMBER OF STUDS:	10	10	10	10	10
BOLT CIRCLE DIAMETER:	11.25"	11.25"	11.25"	11.25"	11.25"
WHEEL MATERIAL:	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum
DUAL / SUPER SINGLE: (SS) Short Stud (LS) Long Stud	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)
LUBE TYPE:	☐ SAE 80/90 ☐ Semi-Fluid Grease ☐ Synthetic 75W/90	☐ SAE 80/90 ☐ Synthetic 75W/90	Semi-Fluid Grease	Semi-Fluid Grease	☐ Semi-Fluid Grease ☐ Synthetic 75W/90
SEAL:	☐ Stemco Voyager ☐ Stemco Discover ☐ Hendrickson	Standard	Standard	Standard	No (ConMet Included)
BEARING:	Standard	Standard	Standard	Standard	No (ConMet Included)
SPINDLE NUT:	Standard 3-Piece Nut	PRECISION240® Nut System PRECISION320® Nut System or	PRECISION240 Nut System PRECISION320 Nut System or	PRECISION320 Nut System	Standard 3-Piece Nut
HUBCAP TYPE:	Standard Bolt-On	Standard Aluminum Bolt-On	Standard Aluminum Bolt-On	Corrosion Resistant Bolt-On	Standard Bolt-On
ABSTONE RING:	Yes	Yes	Yes	Yes	Yes

DRUM OPTIONS

DRUM MATERIAL:	☐ Cast	☐ Fused
DRUM DUTY:	☐ Standard	☐ Heavy Duty
DRUM BALANCING:	Balanced	
WHEEL FASTENERS:	☐ Yes ⁷	☐ No

6. Refer to Hendrickson publication L583 Comprehensive Warranty Statement for complete details.

7. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in plastic bag, taped and stretch wrapped to each wheel-end.

HENDRICKSON SUSPENSION AND AXLES AVAILABLE WITH AIR DISC BRAKES (ADB)

SUSPENSION / AXLE MODELS	AVAILABILITY
UTKNT 40K	ADB available



WARNING: IMPROPER WHEELS OR VALVE STEMS can interfere with air disc brakes and cause rapid tire deflation, component damage, loss of vehicle control, property damage or severe personal injury. Use only wheels and valve stems that provide proper running clearance with air disc brakes equipped on the suspension. Contact vehicle manufacturer to determine replacement wheels and valve stems approved for the application.

DISC BRAKES *	*Please refer to L1225 at www.hendrickson-intl.com for more important information to consider when spec'ing air disc brakes.				
	HENDRICKSON MAXX22T™ ADB (Hendrickson Standard)				
CONVERTER DOLLY APPLICATION:	No				
DISC BRAKE APPROVAL:	Approval: 20,000 lb or less GAWR or up to 23,000 lb GAWR with appropriate tire SLR (See L809 for all Brake Certifications)				
PAD / LINING:	ADB 23K GAWR				
BRAKE CHAMBER:	Type 20 / 24 Std				
ABS TONE RING / DUST SHIELD:	Required				
ABS SENSORS (Required):	☐ Bendix 78.7" ☐ Haldex 19.7" ☐ Haldex 78.7" ☐ WABCO 39.4"				
ABS SENSOR LOCATION:	Tandem: ☐ 2 – Front ☐ 2 – Rear ☐ 4 – Both Tridem: ☐ 2 – Front ☐ 2 – Middle ☐ 2 – Rear ☐ 4 – Front & Middle ☐ 4 – Front & Rear ☐ 4 – Middle & Rear ☐ 6 – All				
ROTOR BRAND / MATERIAL:	415mm Cast Iron	415mm Cast Iron	415mm Cast Iron	415mm Cast Iron	415mm Cast Iron
ROTOR MOUNTING:	Inboard	Inboard	Inboard	Inboard	Outboard
RTR® READY-TO-ROLL® WHEEL-END PACKAGES:	☐ Standard Service (1-year Limited Warranty ⁶)	☐ HXL3® Hendrickson Extended-Life System™ (3-year Limited Warranty ⁶)	☐ HXL5® Hendrickson Extended-Life System™ (5-year Limited Warranty ⁶)	☐ HXL7® Hendrickson Extended-Life System™ (7-year Limited Warranty ⁶)	☐ HXL7® Hendrickson Extended-Life System™ (7-year Limited Warranty ⁶)
SPINDLE:	☐ HN ☐ HP	☐ HN ☐ HP	☐ HN ☐ HP	HP	HX
HUB MATERIAL:	☐ Dura-Light Hub® ☐ Ductile Iron	☐ Dura-Light Hub ☐ Ductile Iron	☐ Dura-Light Hub ☐ Ductile Iron	☐ Dura-Light Hub ☐ Ductile Iron	Steel
HUB STYLE:	Hub-Piloted x 10-stud x 11.25" BC for 22.5" and 24.5" tires				
WHEEL MATERIAL:	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel / Aluminum
DUAL / SUPER SINGLE: (SS) Short Stud (LS) Long Stud	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (LS)
LUBE TYPE:	☐ SAE 80/90 ☐ Semi-Fluid Grease ☐ Synthetic 75W/90	☐ SAE 80/90 ☐ Synthetic 75W/90	Semi-Fluid Grease	Semi-Fluid Grease	Semi-Fluid Grease
SEAL:	Standard	Standard	Standard	Standard	Hendrickson Premium
BEARINGS:	Standard	Standard	Standard	Standard	Timken
SPINDLE NUT:	Standard 3-Piece Nut	PRECISION240® Nut System PRECISION320® Nut System or	PRECISION240 Nut System PRECISION320 Nut System or	PRECISION320 Nut System	PRECISION320
HUBCAP TYPE:	Standard Bolt-On	Standard Aluminum Bolt-On	Standard Aluminum Bolt-On	Corrosion Resistant Bolt-On	Corrosion Resistant Bolt-On
WHEEL FASTENERS:	☐ Yes ⁷ ☐ No				

6. Refer to Hendrickson publication L583 Comprehensive Warranty Statement for complete details.

7. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in plastic bag, taped and stretch wrapped to each wheel-end.

DISC BRAKES *		*Please refer to L1225 at www.hendrickson-intl.com for more important information to consider when spec'ing air disc brakes.				
		WABCO PAN22-1 ADB				
CONVERTER DOLLY APPLICATION:	No					
DISC BRAKE APPROVAL:	Approval: Up to 23,000 lb GAWR with appropriate tire SLR (See L809 for all Brake Certifications)					
PAD / LINING:	WABCO 230					
BRAKE CHAMBER:	Type 20/24 Std					
ABS TONE RING / DUST SHIELD:	Required					
ABS SENSORS (Required):	☐ Bendix 78.7" ☐ Haldex 19.7" ☐ Haldex 78.7" ☐ WABCO 39.4"					
ABS SENSOR LOCATION:	Tandem: ☐ 2 – Front ☐ 2 – Rear ☐ 4 – Both Tridem: ☐ 2 – Front ☐ 2 – Middle ☐ 2 – Rear ☐ 4 – Front & Middle ☐ 4 – Front & Rear ☐ 4 – Middle & Rear ☐ 6 – All					
ROTOR BRAND / MATERIAL:	430mm Cast Iron	430mm Cast Iron	430mm Cast Iron	430mm Cast Iron	430mm ConMet Cast Iron	
RTR® READY-TO-ROLL® WHEEL-END PACKAGES:	☐ Standard Service (1-year Limited Warranty ⁶)	☐ HXL3® Hendrickson Extended-Life System™ (3-year Limited Warranty ⁶)	☐ HXL5® Hendrickson Extended-Life System™ (5-year Limited Warranty ⁶)	☐ HXL7® Hendrickson Extended-Life System™ (7-year Limited Warranty ⁶)	☐ ConMet PreSet (5-year Limited Warranty ⁶)	
SPINDLE:	☐ HN ☐ HP	☐ HN ☐ HP	☐ HN ☐ HP	HP	☐ HN ☐ HP	
HUB MATERIAL:	Ductile Iron	Ductile Iron	Ductile Iron	Ductile Iron	ConMet Aluminum	
HUB STYLE:	Hub-Piloted x 10-stud x 11.25" BC for 22.5" and 24.5" tires					
WHEEL MATERIAL:	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	
DUAL / SUPER SINGLE: (SS) Short Stud (LS) Long Stud	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	
LUBE TYPE:	☐ SAE 80/90 ☐ Semi-Fluid Grease ☐ Synthetic 75W/90	☐ SAE 80/90 ☐ Synthetic 75W/90	Semi-Fluid Grease	Semi-Fluid Grease	☐ Semi-Fluid Grease ☐ Synthetic 75W/90	
SEAL:	Standard	Standard	Standard	Standard	No (ConMet Included)	
BEARINGS:	Standard	Standard	Standard	Standard	No (ConMet Included)	
SPINDLE NUT:	Standard 3-Piece Nut	PRECISION240® Nut System PRECISION320® Nut System or	PRECISION240 Nut System PRECISION320 Nut System or	PRECISION320 Nut System	Standard 3-Piece Nut	
HUBCAP TYPE:	Standard Bolt-On	Standard Aluminum Bolt-On	Standard Aluminum Bolt-On	Corrosion Resistant Bolt-On	Standard Bolt-On	
WHEEL FASTENERS:	☐ Yes ⁷ ☐ No					

6. Refer to Hendrickson publication L583 Comprehensive Warranty Statement for complete details.

7. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in plastic bag, taped and stretch wrapped to each wheel-end.

DISC BRAKES *		*Please refer to L1225 at www.hendrickson-intl.com for more important information to consider when spec'ing air disc brakes.					
		KNORR / BENDIX ADB22X-LT					
CONVERTER DOLLY APPLICATION:	No						
DISC BRAKE APPROVAL:	Approval: Up to 23,000 lb GAWR with appropriate tire SLR (See L809 for all Brake Certifications)						
PAD/LINING:	BX276						
BRAKE CHAMBER:	Knorr 18/24 Std						
ABS TONE RING / DUST SHIELD:	Required						
ABS SENSORS (Required):	☐ Bendix 78.7" ☐ Haldex 19.7" ☐ Haldex 78.7" ☐ WABCO 39.4"						
ABS SENSOR LOCATION:	Tandem: ☐ 2 – Front ☐ 2 – Rear ☐ 4 – Both Tridem: ☐ 2 – Front ☐ 2 – Middle ☐ 2 – Rear ☐ 4 – Front & Middle ☐ 4 – Front & Rear ☐ 4 – Middle & Rear ☐ 6 – All						
ROTOR BRAND / MATERIAL:	430mm Knorr Cast Iron	430mm Knorr Cast Iron	430mm Knorr Cast Iron	430mm Knorr Cast Iron	430mm Knorr Cast Iron	430mm ConMet Cast Iron	430mm ConMet Cast Iron
RTR® READY-TO-ROLL® WHEEL-END PACKAGES:	☐ Standard Service (1-year Limited Warranty ⁶)	☐ HXL3® Hendrickson Extended-Life System™ (3-year Limited Warranty ⁶)	☐ HXL5® Hendrickson Extended-Life System™ (5-year Limited Warranty ⁶)	☐ HXL7® Hendrickson Extended-Life System™ (7-year Limited Warranty ⁶)	☐ ConMet PreSet (5-year Limited Warranty ⁶)		
SPINDLE:	☐ HN ☐ HP	☐ HN ☐ HP	☐ HN ☐ HP	HP	☐ HN ☐ HP		
HUB MATERIAL:	Ductile Iron	Ductile Iron	Ductile Iron	Ductile Iron	☐ ConMet AL Splined	☐ ConMet Ductile Iron (HP Only) ☐ ConMet Aluminum	
HUB STYLE:	Hub-Piloted × 10-stud × 11.25" BC for 22.5" and 24.5" tires						
WHEEL MATERIAL:	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum	☐ Aluminum ☐ Steel ☐ Steel / Aluminum		
DUAL / SUPER SINGLE: (SS) Short Stud (LS) Long Stud	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)	☐ Dual ☐ Super Single (SS) ☐ Super Single (LS)		
LUBE TYPE:	☐ SAE 80/90 ☐ Semi-Fluid Grease ☐ Synthetic 75W/90	☐ SAE 80/90 ☐ Synthetic 75W/90	Semi-Fluid Grease	Semi-Fluid Grease	☐ Semi-Fluid Grease ☐ Synthetic 75W/90		
SEAL:	Standard	Standard	Standard	Standard	No (ConMet Included)		
BEARINGS:	Standard	Standard	Standard	Standard	No (ConMet Included)		
SPINDLE NUT:	Standard 3-Piece Nut	PRECISION240® Nut System PRECISION320® Nut System	or PRECISION240 Nut System PRECISION320 Nut System	or PRECISION320 Nut System	PRECISION320 Nut System	Standard 3-Piece Nut	
HUBCAP TYPE:	Standard Bolt-On	Standard Aluminum Bolt-On	Standard Aluminum Bolt-On	Corrosion Resistant Bolt-On	Standard Bolt-On		
WHEEL FASTENERS:	☐ Yes ⁷ ☐ No						

6. Refer to Hendrickson publication L583 Comprehensive Warranty Statement for complete details.

7. Two (2) wheel fasteners factory installed per wheel-end with balance packaged in plastic bag, taped and stretch wrapped to each wheel-end.

ACCESSORY ITEMS	Not included in ULTRAA-K® Model Number — Sold Separately		
STINGER:	☐ Yes	☐ No	Length: 32"
SINGLE AXLE SLIDER REPOSITIONING KIT ⁸ :	☐ Yes	☐ No	
MANUAL DUMP VALVE:	☐ Yes	☐ No	With Enclosure: ☐ Yes ☐ No
STOP BAR:	☐ Yes	☐ No	
UNIVERSAL LOAD SCALE KIT:	☐ Yes	☐ No	

TIREMAAX ^{® 9}									
MODEL TYPE:	☐ CP	☐ PRO			☐ PRO-LB ¹⁰				
SUSPENSION CATEGORY:	N/A				A				
ELECTRICAL CONNECTION:	☐ Delphi Weather Pack (Standard)				☐ Blade Terminals ¹¹				
MODEL TYPE:	CP / PRO				PRO-LB				
TIRE SIZE:	☐ 22.5" ☐ 24.5"				☐ 22.5" ☐ 24.5"				
NUMBER OF AXLES:	2				2				
AXLE STYLE:	Integrated				Integrated				
HUBCAP TYPE:	☐ Hendrickson Bolt-On				☐ Hendrickson Extended Bolt-On ¹²				
LUBE TYPE:	☐ Semi-Fluid Grease				☐ Oil				
WHEEL STYLE / MATERIAL:	☐ Dual / Aluminum				☐ Dual / Steel or Combo		☐ Super Single / Aluminum ¹³ (Outward facing stem; straight hose)		
	☐ Super Single / Steel (Inward facing stem; 180-degree hose)				☐ Super Single / Steel (Outward facing stem; straight hose)				
	☐ Dual / Alcoa ULT36 All Alum				☐ Dual / Alcoa ULT36 Steel Combo				
MODEL TYPE:	CP			PRO		PRO-LB			
COLD TIRE PRESSURE SETTING (PSI):	☐ 70	☐ 100	☐ 85	☐ 105	COLD TIRE PRESSURE SETTING (PSI) AT 17,000 LB:	Dual (Min. PSI = 75)		Super Single (Min. PSI = 90)	
	☐ 75	☐ 105	☐ 90	☐ 110		☐ 85	☐ 105	☐ 100	☐ 115*
	☐ 80	☐ 110	☐ 95	☐ 115		☐ 90	☐ 110*	☐ 105	☐ 120*
	☐ 85	☐ 115	☐ 100	☐ 120		☐ 95	☐ 115*	☐ 110*	
	☐ 90	☐ 120				☐ 100	☐ 120*		
	☐ 95								
							*REQUIRES ENGINEERING APPROVAL		
TIRE HOSE:	☐ Standard				☐ Integral Check Port - 1-Port (22.5" tire size only)		☐ Integral Check Port - 2-Port (22.5" tire size only)		
INDICATOR LIGHT KIT:	☐ LED – 12V with 65-Foot Cable (Standard)				☐ LED – 12V with 35-Foot Cable		☐ LED – 24V with 65-Foot Cable (Export ¹⁴)		☐ No ¹¹
WIRING HARNESS:	☐ Premium, 15-Foot, ABS-Ready		☐ Premium, 3-Foot, ABS-Ready		☐ Standard, 18-Inch, Wiring Adapter Plug		☐ No ¹¹		
AIR PLUMBING KIT:	☐ Manifold		☐ No						
CONTROLLER TANK VALVE:	☐ Yes (CP models only)		☐ No						

8. Hendrickson recommends the use of a Slider Repositioning Kit for all single-axle sliders used in conjunction with fixed suspensions. The kit locks the brakes and dumps the air on the sliding axle for ease of repositioning.

9. When installing TIREMAAX, please contact Hendrickson to verify correct wheel-end component integration.

10. Due to capacity limitations of a typical tractor's compressor, installation of PRO-LB on more than two axles per vehicle combination is not advised.

11. Controllers featuring blade terminals, require the light kit and wiring harness options to be "no".

12. Required for axles with TIREMAAX PRO or PRO-LB equipped with cross-drilled spindles and using the castellated spindle nut. Please verify spindle nut requirements.

13. For aluminum zero-offset wheels with outward facing stem, contact Hendrickson Engineering for applications support.

14. Please note, 12V is used in some export countries. If this is a new venture into a foreign country, please validate voltage requirements with Controls Engineering.

INSTRUCTIONS (cont.)

For complete price and model number information on an ULTRAA-K® slider suspension system, email this form to your account specialist or:

for OEM Customer Service send to Canton_Inside_Sales@hendrickson-intl.com

for Aftermarket Customer Service send to CantonAftermarketCustomerService@hendrickson-intl.com

for Canada send to bramptoncustomerservice@hendrickson-intl.com

Notes

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, operation, service and maintenance instructions.

Call Hendrickson at **866.RIDEAIR (743.3247)** for additional information.



www.hendrickson-intl.com

L1226 Rev U 01-25

© 2014 -2025 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
Fax 800.696.4416

Hendrickson Canada ULC

2825 Argentia Road, Unit #1 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.812.9423

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601