NTRAAX® RCA

Raised-Center Axle System



- Boost trailer productivity
- Increase value
- Optimized design for rear-discharge tankers



INTRAAX® RCA System Features and Benefits

Patented Cam -Tube System™

- Enhances S-cam alignment and helps extend life of brake components
- Short 10-inch S-cam reduces windup and bushing wear for responsive, consistent stopping power

TRI-FUNCTIONAL® Bushing

- Controls vertical, horizontal and roll forces of trailer
- Optimizes ride softness, control and stability

HENDRICKSON



Brake Mounting Hardware

 Welded to trailing arms rather than axle; minimizes axle stress

Raised-Center Axle

Advanced Axle Wrap and Window Weld

Leading structural warranty* supported by a

Provides optimal structural integrity

 Optimized design for rear-discharge tankers. The raised (hump) axle section allows for additional ground clearance for rear discharge tube.

Value-Added Options

- RTR® READY-TO-ROLL® wheel-end options reduce weight, enhance durability and lower maintenance
 - HXL3® Hendrickson Extended-Life 3-year System™ features a three-year limited on-highway warranty*
 - HXL5® Hendrickson Extended-Life 5-year System™ features a five-year limited on-highway warranty*
 - HXL7® Hendrickson Extended-Life 7-year System™ features a seven-year limited on-highway warranty*
- HXS® Hendrickson Extended Service[™] brakes extend intervals between brake service

See RTR READY-TO-ROLL Wheel-End flyer - L1200

*Contact your local Hendrickson representative for complete warranty terms, conditions and limitations.

- Air disc brakes available including Hendrickson MAXX22T™ optimized trailer air disc brake
- TIREMAAX® tire inflation system helps maximize tire life and maintain peak fuel mileage
- Cap-style bushing tube spacers are recommended in tanker applications
- ZMD® ZERO MAINTENANCE DAMPING® exclusive ride technology available on select AAT 23K / 25K RCA models

See TIREMAAX PRO Brochure - L1199 See MAXX22T flyer - L1239 See ZMD flyer - L1209

Specifications

MODEL	SUSPENSION CAPACITY (pounds)	AXLE DIAMETER (inches)	AXLE TRACKS (inches)	RIDE HEIGHTS (inches)	BASE MODEL WEIGHT (pounds)
AAT 23K ¹	23,000	5	71.5 and 77.5	13.5, 14, 15, 16, 17, 18, 19	597
AAT 25K ¹	25,000 ²				
AAL 23K	23,000	5	77.5	8, 9, 12,14, 15, 16, 17, 19	649
AAL 25K	25,000 ²				

^{1.} ZMD is available on select AAT 23K / 25K RCA models. RCA is recommended with limited rebound travel. ZMD is available on models with limited rebound travel and 14" or 16" ride heights only. Additionally, ZMD is available on models with standard travel and 14" - 17" ride heights.

These products are covered by at least one or more U.S. and / or foreign patents and / or pending U.S. and / or foreign patent applications. See Hendrickson for details.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration.

Contact Hendrickson for additional details regarding specifications, applications, capacities, operation, service and maintenance instructions.

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com (1) (in (2) (

TRAILER COMMERCIAL VEHICLE SYSTEMS 2070 Industrial Place SE Canton, OH 44707-2641 USA 866.RIDEAIR (743.3247) Fax 800.696.4416 HENDRICKSON CANADA ULC 2825 Argentia Road, Unit #1 - 4 Mississauga, ON Canada L5N 866 800.668.5360 905.789.1030 • Fax 905.812.9423 HENDRICKSON MEXICANA
Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México CP 76246
+52 442.296.3600 • Fax +52 44<u>2.296.3601</u>

^{2.} Axle rated only for 23,000 pounds. Brakes rated separately.