

H[®] HT[™] SERIES

HT300T SPECIFICATIONS

LIT NO: L90

DATE: March 2022

REVISION: F



HT300T SPECIFICATIONS



APPLICATIONS		
¹ CAPACITY:	30,000 lbs. (13 600 kg)	
TRAILER TYPES:	UNITED STATES AND CANADA Container Chassis Tanker Chip Van Logging Flat Grain Dump	MEXICO, CENTRAL AND SOUTH AMERICA Van Dump Reefer Tanker Container Chassis Logging Chip Van Grain Flat Livestock
AXLE DATA:	5-inch diameter round, 5/8-inch minimum wall, 16.5-inch drum brakes	
AXLE ARRANGEMENT:	Single, tandem: 122-inch maximum axle spacing, tri or quad-axle	
FRAME TYPES:	Steel or aluminum	
BASE MODEL DESCRIPTION:	HT™ Series top-mount suspension, weld-on, wingless frame brackets with QUIK-ALIGN®, cap style bushing tube spacers and extreme service shocks.	
OTHER OPTIONS:	Additional options include bolt-on frame brackets and remote mount shock absorbers. Lift axle options also available. Contact your Hendrickson representative to discuss these.	

SPECIFICATIONS

SUSPENSION — HT300T (Base Models) ³			
RIDE HEIGHT (inches)	JOUNCE (inches)	REBOUND (inches)	WEIGHT ⁴ (pounds)
15	3.4	4.4	355
17	3.3	4.4	380
19	4.2	3.1	391
21	4.3	3.2	402
23	3.5	4.3	429

1. Capacity refers to suspension ratings, except where noted. Ratings for brakes and wheel-end components differ depending upon options chosen.
2. Refer to literature number L980 for Hendrickson axle capacity rating recommendations. A thicker axle wall should be considered in more demanding applications.
3. Other models and options are available.
4. Weight shown does not include the axle.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at 330.489.0045 or 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
330.489.0045 • Fax 800.696.4416

Hendrickson Canada ULC

2825 Argenta Road, Unit #2 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.802.9423

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601

L90 Rev F 03-22

© 1992 - 2022 Hendrickson USA, L.L.C. All Rights Reserved. All trademarks shown are owned by Hendrickson USA, L.L.C., or one of its affiliates, in one or more countries.

Information contained in this literature was accurate at the time of publication. Product changes may have been made after the copyright date that are not reflected.

Printed in United States of America