

HENDRICKSON USE ONLY

ORDERING GUIDE

HT™ SERIES 25K/30K UNDERSLUNG and Y-BEAM SUSPENSIONS

LIT NO: L555

DATE: January 2025

REVISION: N

FORM INSTRUCTIONS

For complete price and model number information on an HT250US, HT300US or HT300YB suspension system, email this form to the appropriate contact (see page 3). For additional assistance, please call toll-free 866.RIDEAIR (743.3247) in the U.S. or 800.668.5360 in Canada.

TO:	FROM:	COMPANY NAME:	
DATE:	PHONE:	FAX:	EMAIL:

SAME AS:	EXCEPT:
-----------------	----------------

SUSPENSION

SUSPENSION MODEL (capacity):	<input type="checkbox"/> HT250US (25K)	<input type="checkbox"/> HT300US (30K)	<input type="checkbox"/> HT250UB (25K) Air Disc Brake Only
AXLE CONNECTION:	None		
RIDE HEIGHT (inches):	<input type="checkbox"/> 3.5" (25K only)	<input type="checkbox"/> 4" (25K only)	<input type="checkbox"/> 5.5" <input type="checkbox"/> 6.5" <input type="checkbox"/> 7.5" <input type="checkbox"/> 9"
	<input type="checkbox"/> 12"	<input type="checkbox"/> 14"	<input type="checkbox"/> 17" (30K only)
TRAVEL:	<input type="checkbox"/> Standard	<input type="checkbox"/> Limited Jounce	<input type="checkbox"/> Extended Rebound
FRAME ATTACHMENT:	<input type="checkbox"/> Weld-On	<input type="checkbox"/> Bolt-On	<input type="checkbox"/> Other
	MOUNTING BOLT SIZE:		<input type="checkbox"/> 0.500" <input type="checkbox"/> 0.625" ¹
AIR SPRING PSI RANGE:	<input type="checkbox"/> Standard	<input type="checkbox"/> High Pressure (25K only)	
AIR SPRING MOUNTING STUD:	<input type="checkbox"/> Single Combo Stud (25K Std)	<input type="checkbox"/> Single Combo Stud Rotated ^{2,3}	<input type="checkbox"/> Dual Combo Stud (30K Std)
AIR SPRING MOUNTING PLATE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Rotated (25K only)	<input type="checkbox"/> None
SHOCK ABSORBER:	<input type="checkbox"/> Standard	<input type="checkbox"/> Extended Service / High Damping ¹	
SHOCK MOUNTING:	<input type="checkbox"/> Forward Upper Mount (Standard)	<input type="checkbox"/> Remote Mount	
SHOCK STRAPS:	<input type="checkbox"/> Yes	<input type="checkbox"/> No	
FRAME BRACKET TO BEAM:	<input type="checkbox"/> Assembled	<input type="checkbox"/> Non-Assembled	<input type="checkbox"/> Separate Frame Kit
TIRE / BRAKE SIZE: (To determine U-bolt)	<input type="checkbox"/> 17.5" / 12.25" (25K only)	<input type="checkbox"/> 19.5" / 15.0" or larger	
FRAME BRACKET SUPPORT (C-Channel):	<input type="checkbox"/> Weld-on C-Channel	<input type="checkbox"/> Customer Supplied	
HIGH CONTROL SUSPENSION⁴:	<input type="checkbox"/> Yes	<input type="checkbox"/> No	
AXLE STYLE:	<input type="checkbox"/> Standard	<input type="checkbox"/> Steerable (HT250US only)	
U-BOLT LOCATION:	<input type="checkbox"/> In Parts Box	<input type="checkbox"/> Separate Kit	
BRAKE TYPE:	<input type="checkbox"/> Drum	<input type="checkbox"/> Air Disc Brake (HT250UB Only)	
CAM TUBE:	<input type="checkbox"/> Yes	<input type="checkbox"/> No	
BEAM COATING (Suspension Coating):	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None	
FRAME COMPONENTS COATING: (Frame Bracket Coating)	<input type="checkbox"/> Standard Black Primer	<input type="checkbox"/> None / Do not paint frame brackets	

1. Required for HT300US suspension.
2. Available for 25K and 30K models.
3. 30K rotated stud uses a high pressure air spring. Does not equalize with the standard HT300US air spring option.
4. High control suspensions are recommended for single-axle trailers in multi-trailer combinations, all dollies and full trailers with two single axles. Not for use on multiple-axle trailers.
NOTE: Some combinations may not be compatible or available.





Are you ordering a Y-Beam suspension? No Yes (continue below)

SUSPENSION	
SUSPENSION MODEL (capacity):	<input type="checkbox"/> HT250YS ⁵ (25K Y-Beam) <input type="checkbox"/> HT300YB⁶ (30K Y-Beam)
AXLE CONNECTION:	None
RIDE HEIGHT (inches):	<input type="checkbox"/> 6.5" <input type="checkbox"/> 7.5" <input type="checkbox"/> 9"
TRAVEL:	Standard
FRAME ATTACHMENT:	Y-Beam
AIR SPRING PSI RANGE:	<input type="checkbox"/> Standard <input type="checkbox"/> High Pressure (25K Only)
AIR SPRING MOUNTING STUD:	<input type="checkbox"/> Single Combo Stud (25K Std) <input type="checkbox"/> Single Combo Stud Rotated^{7,8} <input type="checkbox"/> Dual Combo Stud (30K Std)
AIR SPRING MOUNTING PLATE:	<input type="checkbox"/> Standard <input type="checkbox"/> None
SHOCK ABSORBER:	Standard
SHOCK MOUNTING:	Forward Upper Mount (Standard)
SHOCK STRAPS:	<input type="checkbox"/> Yes <input type="checkbox"/> No
FRAME BRACKET TO BEAM:	Non-Assembled
TIRE / BRAKE SIZE: (To determine U-bolt)	<input type="checkbox"/> 17.5" / 12.25" or larger <input type="checkbox"/> 19.5" / 15.0" or larger
FRAME BRACKET SUPPORT (C-Channel):	None (Y-Beam)
HIGH CONTROL SUSPENSION:	No
AXLE STYLE:	Standard
BRAKE TYPE:	Drum Only (Air disc brakes are not available)
BEAM COATING (Suspension Coating):	<input type="checkbox"/> Standard Black Primer <input type="checkbox"/> None
FRAME COMPONENTS COATING: (Frame Bracket Coating)	None

5. For use in conjunction with HT250US suspensions.

6. For use in conjunction with HT300US suspensions.

7. Available for 25K and 30K models.

8. 30K rotated stud uses a high pressure air spring. Does not equalize with the standard HT300US air spring option.

