

HHT™ SERIES

HT300US SPECIFICATIONS

LIT NO: L1229

DATE: April 2023

REVISION: C





APPLICATIONS		
*CAPACITY	30,000 lbs. (13 600 kg)	
TRAILER TYPES	Chip Van Platform Flat Auto Hauler Lowboy/Drop Deck Container Chassis Dump Logging Tanker Livestock Grain <i>Refer to "L707 Application Guide" for Recommended Applications</i>	
AXLE DATA	5-inch diameter round, 3/4-inch wall, 15-inch and 16.5-inch brakes	
AXLE ARRANGEMENT	Single, tandem: 122-inch maximum axle spacing Tri or quad: 144-inch maximum total spacing	
FRAME TYPES	Steel only; 96-inch or 102-inch wide trailers	
BASE MODEL DESCRIPTION:	HT™ Series underslung standard travel suspension, 6.5-inch ride height, weld-on, wingless frame brackets with QUIK-ALIGN® and forward mounted shocks standard with shock straps.	
**BASE MODEL WEIGHT:	375 lbs.	
OTHER OPTIONS:	Additional options include bolt-on frame brackets, remote mount shock absorbers and limited jounce travel. Contact your Hendrickson representative to discuss these and other product options such as single combo rotated stud A/S.	

* Capacity refers to suspension ratings, except where noted. Ratings for brakes and wheel-end components differ depending upon options chosen.

** Weight shown does not include the axle or the frame bracket crossmember.

SPECIFICATIONS

SUSPENSION — HT300US		
RIDE HEIGHT (inches)	JOUNCE ^{1,2} (inches)	REBOUND ^{1,2} (inches)
5.5	2.0	4.7
6.5	3.0	3.7
7.5	3.1	6.0
9.0	4.6	4.5
12.0	4.9	4.0
14.0	5.0	4.0
17.0	5.5	3.5

¹ Jounce, rebound and weight figures shown are for models with standard weld-on hangers and standard shock absorbers. These values differ slightly for other models and options. Contact Hendrickson for more information.

² Limited axle travel configurations and extended rebound 6.5-inch ride height models are also available.

Actual product performance may vary depending upon vehicle configuration, operation, service and other factors.

All applications must comply with applicable Hendrickson specifications and must be approved by the respective vehicle manufacturer with the vehicle in its original, as-built configuration. Contact Hendrickson for additional details regarding specifications, applications, capacities, and operation, service and maintenance instructions.

Call Hendrickson at 866.RIDEAIR (743.3247) for additional information.



www.hendrickson-intl.com

TRAILER COMMERCIAL VEHICLE SYSTEMS

2070 Industrial Place SE
Canton, OH 44707-2641 USA
866.RIDEAIR (743.3247)
Fax 800.696.4416

Hendrickson Canada ULC

2825 Argenta Road, Unit #2 - 4
Mississauga, ON Canada L5N 8G6
800.668.5360
905.789.1030 • Fax 905.812.9423

Hendrickson Mexicana

Circuito El Marqués Sur #29
Parque Industrial El Marqués
Pob. El Colorado, Municipio El Marqués,
Querétaro, México C.P. 76246
+52 (442) 296.3600 • Fax +52 (442) 296.3601